



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/618,113	07/11/2003	Rajeev Joshi	11948.21	8697

27966 7590 11/22/2006

KENNETH E. HORTON  
KIRTON & MCCONKLE  
60 EAST SOUTH TEMPLE  
SUITE 1800  
SALT LAKE CITY, UT 84111

EXAMINER

ZARNEKE, DAVID A

ART UNIT

PAPER NUMBER

2891

DATE MAILED: 11/22/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

## Office Action Summary

Application No.

10/618,113

Applicant(s)

JOSHI ET AL.

Examiner

David A. Zarneke

Art Unit

2891

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 12 September 2006.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 20-48 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 20-48 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_

- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

**DAVID ZARNEKE**  
**PRIMARY EXAMINER**

## **DETAILED ACTION**

### ***Response to Arguments***

Applicant's arguments filed 9/12/06 have been fully considered but they are not persuasive.

First, it is argued that the elimination of the UBM from the pad is not legally or technically supported. That it hasn't been substantiated that a skilled artisan, not the examiner, considers whether the function of the UBM is required to make the pad operate. This is because it would not have been obvious to remove the UBM it improves the wettability and adhesion of the pad to the solder ball.

Please note that the rejection is that the UBM can be removed from the pad without any loss of function and that the UBM is not desired or required. The rejection states that the UBM is not required to make the pad operate. An electrical pad can operate without a UBM. While the UBM may make the pad operate better, as noted in the response, the pad can operate without the UBM nonetheless.

The second argument is that the combination of Higgins and Chakravorty would only increase the thickness, complexity and cost of the process of making the package.

Please note that Chakravorty lists many benefits of using this configuration. It states that not only is the package more compact, but lowers inductance, eliminates processing steps, uses fewer materials and therefore reduces costs (4, 41+ & 5, 63+). The fact that applicant has attacked one of these benefits, doesn't mean that it would have not been obvious to use this configuration in Higgins.

Art Unit: 2891

The third and final argument is that a skilled artisan would not have used an additional solder ball in the configuration of Higgins.

Please note that the invention of Chakravorty proves otherwise. Chakravorty provides many and varied reasons why a skilled artisan would use, and benefit from, this configuration (4, 41+ & 5, 63+).

For the reasons provided above in response to the arguments presented and for the reasons stated in the rejection of the previous office action, and re-stated below, the claims stand as finally rejection.

### ***Claim Rejections - 35 USC § 103***

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of

Art Unit: 2891

the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

Claims 20, 22 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (Figure 1) teaches a method of making a wafer-level chip scale package, comprising:

- providing a chip pad (14) over a substrate (11);
- providing a re-distributed line (RDL) pattern (16) on the chip pad;
- providing an insulating layer (18) covering a portion of the RDL pattern, wherein the insulating layer comprises a non-polymeric dielectric material (2, 65+); and
- providing a stud bump (20) directly on the portion of the RDL pattern not covered by the insulating layer.

Regarding the bump being "directly" on the RDL, Higgins discloses the claimed invention except for the inclusion of a UBM pad. It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

Art Unit: 2891

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well-known and readily obvious to one of ordinary skill in the art.

Regarding claim 22, Higgins teaches the insulating layer comprises SiN (2, 65+).

With respect to claim 23, as noted above, while Higgins teaches using a UBM, it would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Claims 24, and 26-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (Figure 1) teaches a method of making a wafer-level chip scale package, comprising:

- providing a substrate (11) with a passivation layer (12) on a portion thereof;

- forming a chip pad (14) on a portion of the substrate not containing the passivation layer;

- forming a metal layer (16) on the chip pad and a portion of the passivation layer;

forming an insulating layer (18) on a portion of the metal layer, wherein the insulating layer comprises a non-polymeric dielectric material (2, 65+); and

forming a stud bump (20) directly on the portion of the metal layer not covered by the insulating layer.

Regarding the bump being "directly" on the RDL, it would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Regarding claim 26, Higgins teaches the insulating layer comprises SiN (2, 65+).

With respect to claims 27, while Higgins fails to expressly state that the insulating layer is formed without using a high temperature curing process, SiN inherently uses a low temperature curing process.

With respect to claim 28, as noted above, while Higgins teaches using a UBM, it would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Claim 32 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (Figure 1) teaches a method of making a package semiconductor device, comprising:

- providing a chip pad (14) over a substrate (11);
- providing a re-distributed line (RDL) pattern (16) on the chip pad;
- providing an insulating layer (18) covering a portion of the RDL pattern, wherein the insulating layer comprises a non-polymeric dielectric material (2, 65+); and
- providing a stud bump (20) directly on the portion of the RDL pattern not covered by the insulating layer.

Regarding the bump being "directly" on the RDL, It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention



Art Unit: 2891

inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Claim 33 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (Figure 1) teaches a method of making a wafer-level chip scale package, comprising:

providing a packaged semiconductor device (10) containing a chip pad (14) over a substrate (11), a re-distributed line (RDL) pattern (16) on the chip pad, an insulating layer (18) covering a portion of the RDL pattern with the insulating layer comprising a non-polymeric dielectric material (2, 65+), and then providing a stud bump (20) directly on the portion of the RDL pattern not covered by the insulating layer; and mounting the packaged semiconductor device on a circuit board (50).

Regarding the bump being "directly" on the RDL, It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284):

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Art Unit: 2891

Claims 34, 38-40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (figure 1) teaches a method for making wafer-level chip scale package, comprising:

- providing a chip pad [12] over a substrate [11];
- providing a re-distributed line (RDL) pattern [16] on the chip pad;
- providing an insulating layer [18] covering a portion of the RDL pattern; and
- providing a stud bump [20] on the portion of the RDL pattern not covered by the insulating layer without using an under bump metal.

Higgins discloses the claimed invention except for the inclusion of a UBM pad. It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well-known and readily obvious to one of ordinary skill in the art.

Regarding claims 38-40, Higgins teaches the insulating layer [18] comprises a non- polymeric dielectric material, such as silicon nitride (2, 65+), which does not require a high temperature curing process.

Claims 41, 45-47 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins).

Higgins (figure 1) teaches a method for making wafer-level chip scale package, comprising:

- providing a chip pad [12] over a substrate [11];
- providing a single layer re-distributed line (RDL) pattern [16] on the chip pad;
- providing an insulating layer [18] covering a portion of the RDL pattern; and
- providing a stud bump [20] on the portion of the RDL pattern not covered by the insulating layer.

Regarding the bump being “directly” on the RDL, It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well known and readily obvious to one of ordinary skill in the art.

Regarding claims 45-47, Higgins teaches the insulating layer [18] comprises a non-polymeric dielectric material, such as silicon nitride (2, 65+), which does not require a high temperature curing process.

Claim 21 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405, as applied to claim 20 above, and further in view of Chakravorty, US Patent 6,350,668.

Higgins fails to teach the method further comprising providing a solder ball on the stud bump.

Chakravorty (figure 8d) teaches the use of a solder ball (313) on a solder stud (311).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ball on the stud of Chakravorty in the invention of Higgins because both methods are known equivalent techniques used to attach chips to other substrates.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

Claims 25 and 29-31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405, as applied to claim 24 above, and further in view of Chakravorty, US Patent 6,350,668.

Regarding claim 25, Higgins fails to teach the method further comprising providing a solder ball on the stud bump.

Chakravorty (figure 8d) teaches the use of a solder ball (313) on a solder stud (311).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ball on the stud of Chakravorty in the invention of Higgins because both methods are known equivalent techniques used to attach chips to other substrates.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

With respect to claims 29 and 30, Higgins fails to teach forming the stud bump by electroplating or by wire bonding (claims 29), wherein the stud bump is formed by wire bonding a Pd coated copper wire to the RDL pattern using a capillary (claim 30).

Chakravorty teaches the solder stud (311) can be formed using a wire bonder (9, 16+).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the wire bonder of Chakravorty in the invention of Higgins because wire bonding is a known equivalent technique used to deposit metals.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

Though Chakravorty fails to teach the use of a Pd coated copper wire, it would have been obvious to use a Pd coated copper wire because it is a conventionally known in the art material used to form stud bumps.

The use of conventional materials to perform there known functions in a conventional process is obvious (MPEP 2144.07).

As to claim 31, the stud bump being coined shaped is an obvious matter of design choice. Design choices and changes of size and shape are generally recognized as being within the level of ordinary skill in the art (MPEP 2144.04(I), (IVA) & (IVB)).

Claims 35-37 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405, as applied to claim 34 above, and further in view of Chakravorty, US Patent 6,350,668.

Regarding claim 35, Higgins fails to teach the method further comprising providing a solder ball on the stud bump.

Chakravorty (figure 8d) teaches the use of a solder ball (313) on a solder stud (311).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ball on the stud of Chakravorty in the invention of Higgins because both methods are known equivalent techniques used to attach chips to other substrates.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin

Art Unit: 2891

125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

With respect to claims 36 and 37, Higgins fails to teach forming the stud bump by electroplating or by wire bonding (claims 29), wherein the stud bump is formed by wire bonding a Pd coated copper wire to the RDL pattern using a capillary (claim 30).

Chakravorty teaches the solder stud (311) can be formed using a wire bonder (9, 16+).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the wire bonder of Chakravorty in the invention of Higgins because wire bonding is a known equivalent technique used to deposit metals.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

Though Chakravorty fails to teach the use of a Pd coated copper wire, it would have been obvious to use a Pd coated copper wire because it is a conventionally known in the art material used to form stud bumps.

The use of conventional materials to perform there known functions in a conventional process is obvious (MPEP 2144.07).

Claims 42-44 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405, as applied to claim 41 above, and further in view of Chakravorty, US Patent 6,350,668.

Regarding claim 35, Higgins fails to teach the method further comprising providing a solder ball on the stud bump.

Chakravorty (figure 8d) teaches the use of a solder ball (313) on a solder stud (311).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ball on the stud of Chakravorty in the invention of Higgins because both methods are known equivalent techniques used to attach chips to other substrates.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

With respect to claims 36 and 37, Higgins fails to teach forming the stud bump by electroplating or by wire bonding (claims 29), wherein the stud bump is formed by wire bonding a Pd coated copper wire to the RDL pattern using a capillary (claim 30).

Chakravorty teaches the solder stud (311) can be formed using a wire bonder (9, 16+).



Art Unit: 2891

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the wire bonder of Chakravorty in the invention of Higgins because wire bonding is a known equivalent technique used to deposit metals.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (Ex parte Novak 16 USPQ 2d 2041 (BPAI 1989); In re Mostovych 144 USPQ 38 (CCPA 1964); In re Leshin 125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

Though Chakravorty fails to teach the use of a Pd coated copper wire, it would have been obvious to use a Pd coated copper wire because it is a conventionally known in the art material used to form stud bumps.

The use of conventional materials to perform there known functions in a conventional process is obvious (MPEP 2144.07).

Claim 48 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higgins, III, US Patent 6,294,405 (hereafter Higgins), in view of Chakravorty, US Patent 6,350,668.

Higgins (figure 1) teaches a method for making wafer-level chip scale package, comprising:

- providing a chip pad [12] over a substrate [11];

- providing a re-distributed line (RDL) pattern [16] on the chip pad without using an under bump metal;

- providing an insulating layer [18] covering a portion of the RDL pattern; and

providing a stud bump [20] on the portion of the RDL pattern not covered by the insulating layer without using an under bump metal.

Higgins discloses the claimed invention except for the inclusion of a UBM pad. It would have been obvious to one of ordinary skill in the art at the time of the invention to omit the UBM pad since it has been held that the omission of an element and its function in a combination where the remaining elements perform the same functions as before involves only routine skill in the art (*In re Karlson*, 136 USPQ 1284).

The invention of Higgins would still operate without the UBM pad. Its exclusion from Higgins, along with the function of the UBM layer, would not make the invention inoperable and would have been well-known and readily obvious to one of ordinary skill in the art.

Higgins fails to teach the method further comprising providing a solder ball on the stud bump.

Chakravorty (figure 8d) teaches the use of a solder ball (313) on a solder stud (311).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ball on the stud of Chakravorty in the invention of Higgins because both methods are known equivalent techniques used to attach chips to other substrates.

The substitution of one known equivalent technique for another may be obvious even if the prior art does not expressly suggest the substitution (*Ex parte Novak* 16 USPQ 2d 2041 (BPAI 1989); *In re Mostovych* 144 USPQ 38 (CCPA 1964); *In re Leshin*

125 USPQ 416 (CCPA 1960); Graver Tank & Manufacturing Co. V. Linde Air Products Co. 85 USPQ 328 (USSC 1950).

***Conclusion***

**THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).


A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than **SIX MONTHS** from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to David A. Zarneke whose telephone number is (571)-272-1937. The examiner can normally be reached on M-Th 7:30 AM-6 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, William Baumeister can be reached on (571)-272-1722. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2891

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



David A. Zarneke  
Primary Examiner  
November 13, 2006